

DESCRIPTION and USES

Industrial Finishes Rapid-Drying Interior/Exterior High-Gloss Enamel is a heavy-duty, gloss enamel that features rapid speed of dry. Available in Safety Yellow and Red colors. Excellent for use as a multi-purpose, fast-drying finish on parts, machinery, equipment, or wherever a durable, fast-drying paint is needed. Although this paint has a very fast air dry, it can be forced dry with heat when used as an OEM finish. This paint is suitable for both interior and exterior applications.

PREPARATION

SURFACE PREPARATION: All surfaces must be dry, free of dirt, grease, rust and loose paint. Rough surfaces should be smoothed with sandpaper. Prime bare surfaces with the recommended primer. When painting over previously painted surfaces, apply a small sample area to test for lifting.

APPLICATION

Industrial Finishes Rapid-Drying Interior/Exterior High-Gloss Enamel is best applied with conventional, HVLP or airless spray. Small areas may be rolled or brushed. Use as supplied for brushing. Do not apply at temperatures above 90°F or below 55°F.

CLEAN UP

Clean tools immediately after use with specified clean up solvent. Use same clean up solvent to clean dried product off equipment.

COLORS

This product is available in Safety Yellow and Red colors.

REGULATORY INFORMATION

This product is intended for professional use only, and due to VOC restrictions is not suitable for in-place architectural use.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

For complete safety information, refer to the SAFETY DATA SHEET for this product.

TECHNICAL DATA

Finish:	High Gloss
Vehicle Type:	Alkyd Resin
Weight Solids:	41-47% (varies with color)
Volume Solids:	34-36% (varies with color)
Density:	8.1-8.7 lb/gallon
Coverage:	300 – 400 SF/Gallon
Dry Time:	
<i>Touch:</i>	5-10 minutes
<i>Recoat:</i>	3-4 hours
Clean Up:	Xylene
VOC:	Less than 575 g/L

PRODUCT CODE INFORMATION

40420	Rapid-Drying Int/Ext High-Gloss Enamel – Red
40460	Rapid-Drying Int/Ext High-Gloss Enamel – Safety Yellow