

DESCRIPTION and USES

This product is a high-hiding, alkyd primer suitable for priming and sealing porous interior construction materials such as wood and plaster.

It should not be used as a primer coat on drywall except as a base coat for wallpaper. This product has very good adhesion over existing finishes so it serves well as an undercoat over old enameled or varnished surfaces. It sands easily and has excellent holdout under gloss or semi-gloss finishes and is suitable for use under alkyd or latex finish coats. May be tinted with up to 6 ounces per gallon of universal colorant to approximate finish coat color for better 2 coat work.

SURFACE PREPARATION

All surfaces must be clean and dry. New wood should be smoothed, if necessary, by sanding. Old painted or varnished surfaces are best prepared by sanding or washing with a surface preparation liquid. Patch all cracks and holes before priming.

APPLICATION

Apply a full, liberal coat with a brush or roller. On very porous surfaces, 2 coats will provide the best base for the finish coat. Allow to dry completely before sanding or finish coating. Use as supplied. DO NOT THIN.

SAFETY INFORMATION

For complete safety information, refer to the SAFETY DATA SHEET for this product.

COLORS

White (May be tinted with up to 4 oz. Universal Colorant)

TECHNICAL DATA

Vehicle Type:	Soya Alkyd Resin
Volume Solids:	56%
Coverage:	200 – 400 SF/Gallon
Dry Time:	
<i>Touch:</i>	4 Hours
<i>Recoat:</i>	12 – 16 Hours
VOC:	Less than 350 g/l
Clean Up:	Paint Thinner (Mineral Spirits)

PRODUCT CODE INFORMATION

44010

Pro-Flo Primer-Undercoater—White

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

RepcoLite Paints, Inc.

473 W. 17th St.

Holland, MI 49423

(616) 396-1275

www.repcolite.com