

## DESCRIPTION and USES

This fast drying, multi-purpose primer can be used on many porous construction materials such as wood, drywall, plaster, hardboard and other composite materials. It is not affected by moisture when dry, so it can be used inside or outside. Do not use as a primer for ferrous metals. This primer effectively seals back smoke, pen and pencil, and water stains. Its quick dry feature means that it can normally be recoated in 45 to 60 minutes with alkyd or latex-based paints and enamels. May be tinted with up to 4 ounces per gallon of RepcoLite Alkyd Colorant to approximate finish coat color for better 2 coat work.

## SURFACE PREPARATION

All surfaces to be primed must be clean and dry. Old painted or varnished surfaces should be prepared by sanding and/or washing with a surface preparation liquid. Patch holes and cracks before priming.

## APPLICATION

Apply with a brush, roller or spray. Two coats may be necessary over badly soiled or stained areas. Apply as supplied. DO NOT THIN.

## SAFETY INFORMATION

**NOTICE:** Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. For complete safety information, refer to the SAFETY DATA SHEET for this product.

## COLORS

White (May be tinted with up to 4 oz. of RepcoLite Alkyd Colorant per gallon).

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

## TECHNICAL DATA

<b>Vehicle Type:</b>	Vinyl Toluene Alkyd Copolymer
<b>Volume Solids:</b>	42%
<b>Coverage:</b>	200 – 400 SF/Gallon (depending on surface porosity)
<b>Dry Time:</b>	
<i>Touch:</i>	15-30 Minutes
<i>Recoat:</i>	45-60 Minutes
<b>VOC:</b>	Less than 450 g/l
<b>Clean Up:</b>	Mineral Spirits (Paint Thinner)

## PRODUCT CODE INFORMATION

44210

Zip Prime – White

**RepcoLite Paints, Inc.**  
473 W. 17<sup>th</sup> St.  
Holland, MI 49423  
(616) 396-1275  
[www.repcolite.com](http://www.repcolite.com)