

## DESCRIPTION and USES

This 100% acrylic paint will provide a durable finish on exterior vertical surfaces. It offers superior fade resistance, optimized mold and mildew control, and low temperature cure (as low as 36°F). It is self-priming and is low VOC. Endura Satin Sheen is a premium exterior paint for use on vinyl, trim, metal, masonry and many other surfaces where a longlasting finish is required. With proper preparation, this product may be used on aluminum or vinyl siding. Surface dirt is easily washed off this tough 100% acrylic finish paint. This paint dries quickly and tools are easily cleaned after use with soap and water.

## SURFACE PREPARATION

All surfaces to be painted must be clean and free of standing water. Slightly damp surfaces can be painted. All bare surfaces must be primed with the recommended primer.

## APPLICATION

Apply with a brush, roller or airless spray. During warm, windy weather dampening the surfaces with a mist of water will aid application. Avoid painting on hot surfaces or direct sunlight.

## SAFETY INFORMATION

For complete safety information, refer to the SAFETY DATA SHEET for this product.

## COLORS

This product is available in white and all *Color Studio* and *Color Folio* Colors.

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

## TECHNICAL DATA

<b>Finish:</b>	Semi Gloss
<b>Vehicle Type:</b>	100% Acrylic Latex
<b>Volume Solids:</b>	31%
<b>Coverage:</b>	200 – 400 SF/Gallon (depending on surface porosity).
<b>Dry Time:</b>	
<i>Touch:</i>	45 Minutes
<i>Recoat:</i>	4 Hours (recoat times will be slowed by low temperatures and/or high humidity).
<b>Primer:</b>	
<i>Masonry:</i>	44610 Sprayable Block Filler
<i>Pour Concrete:</i>	Self Prime
<i>Non-Ferrous Metals:</i>	44810 QD Rust Inhibitive Primer 44510 Zip Prime-WB Primer
<i>Ferrous Metals:</i>	44917 Metl-Clad Metal Primer
<i>Wood:</i>	44510 Zip Prime-WB 44710 #65 Exterior Primer
<b>VOC:</b>	Less than 380 g/l
<b>Clean Up:</b>	Water

## PRODUCT CODE INFORMATION

46010	Endura—White Base
46002	Endura—342 Base
46003	Endura—343 Base
46006	Endura—346 Base

### RepcoLite Paints, Inc.

473 W. 17<sup>th</sup> St.

Holland, MI 49423

(616) 396-1275

[www.repcolite.com](http://www.repcolite.com)