



# Alkyd Traffic Marking Paint

## Product Data Sheet

### DESCRIPTION and USES

A very fast drying lead-free alkyd-based paint intended to mark roadways, parking lots, aisles, hazardous areas, etc. on concrete or bituminous pavement. Available in high visibility White or Yellow colors. May be used as a binder with glass beads for reflectorized marking. This paint has shown significantly better durability compared to competitive products.

### SURFACE PREPARATION

Sweep or vacuum surfaces to remove loose dirt. Surface must be dry and oil free. New concrete and bituminous surfaces should cure for 4 weeks before marking. Freshly sealed asphalt pavement must be completely dry before striping.

### APPLICATION

This product is normally applied with air or airless spray marking equipment, however it may be applied with a brush or roller. Apply only on dry surfaces when humidity is below 85% and temperature is above 40°F. Thinning this product will bring it out of compliance with current VOC regulations. DO NOT THIN.

### SAFETY INFORMATION

**NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

For complete safety information, refer to the SAFETY DATA SHEET for this product.

### COLORS

White, Black, Handicap Blue and Yellow.

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

### TECHNICAL DATA

<b>Finish:</b>	Flat
<b>Vehicle Type:</b>	Alkyd Resin
<b>Volume Solids:</b>	58%
<b>Coverage:</b>	350 Feet of standard 4" line. (Coverage may vary with surface profile).
<b>Dry Time:</b>	
<i>Touch:</i>	15 – 30 Minutes
<b>VOC:</b>	Less than 450 g/l
<b>Clean Up:</b>	VMP Naptha

### PRODUCT CODE INFORMATION

47610	Alkyd Traffic Marking—White
47630	Alkyd Traffic Marking—Handicap Blue
47660	Alkyd Traffic Marking—Yellow
47670	Alkyd Traffic Marking—Black

#### RepcoLite Paints, Inc.

473 W. 17<sup>th</sup> St.  
Holland, MI 49423  
(616) 396-1275

[www.repcolite.com](http://www.repcolite.com)